

# PRODUCT TEMPLATE

Item: DEC12

Size: 3 3/8" x 2 1/8"

job:0000-Name (f)

job:0000-Name (b)

## DECIMAL EQUIVALENTS

| DECIMALS        | MILLIMETERS    | DECIMALS | MILLIMETERS      |        |
|-----------------|----------------|----------|------------------|--------|
| $\frac{1}{64}$  | 0.015625       | 0.397    | 0.015625         | 13.097 |
| $\frac{2}{64}$  | 0.03125        | 0.794    | 0.03125          | 13.494 |
| $\frac{3}{64}$  | 0.046875       | 1.191    | 0.046875         | 13.891 |
| $\frac{4}{64}$  | 0.0625         | 1.588    | 0.0625           | 14.288 |
| $\frac{5}{64}$  | 0.078125       | 1.984    | 0.078125         | 14.684 |
| $\frac{6}{64}$  | 0.09375        | 2.381    | 0.09375          | 15.081 |
| $\frac{7}{64}$  | 0.109375       | 2.778    | 0.109375         | 15.478 |
| $\frac{8}{64}$  | 0.1250         | 3.175    | 0.1250           | 15.875 |
| $\frac{9}{64}$  | 0.140625       | 3.572    | 0.140625         | 16.272 |
| $\frac{10}{64}$ | 0.15625        | 3.969    | 0.15625          | 16.669 |
| $\frac{11}{64}$ | 0.171875       | 4.366    | 0.171875         | 17.066 |
| $\frac{12}{64}$ | 0.1875         | 4.763    | 0.1875           | 17.463 |
| $\frac{13}{64}$ | 0.203125       | 5.159    | 0.203125         | 17.859 |
| $\frac{14}{64}$ | 0.21875        | 5.556    | 0.21875          | 18.256 |
| $\frac{15}{64}$ | 0.234375       | 5.953    | 0.234375         | 18.653 |
| $\frac{16}{64}$ | 0.2500         | 6.350    | 0.2500           | 19.050 |
| $\frac{17}{64}$ | 0.265625       | 6.747    | 0.265625         | 19.447 |
| $\frac{18}{64}$ | 0.28125        | 7.144    | 0.28125          | 19.844 |
| $\frac{19}{64}$ | 0.296875       | 7.541    | 0.296875         | 20.241 |
| $\frac{20}{64}$ | 0.3125         | 7.938    | 0.3125           | 20.638 |
| $\frac{21}{64}$ | 0.328125       | 8.334    | 0.328125         | 21.034 |
| $\frac{22}{64}$ | 0.34375        | 8.731    | 0.34375          | 21.431 |
| $\frac{23}{64}$ | 0.359375       | 9.128    | 0.359375         | 21.828 |
| $\frac{24}{64}$ | 0.3750         | 9.525    | 0.3750           | 22.225 |
| $\frac{25}{64}$ | 0.390625       | 9.922    | 0.390625         | 22.622 |
| $\frac{26}{64}$ | 0.40625        | 10.319   | 0.40625          | 23.019 |
| $\frac{27}{64}$ | 0.421875       | 10.716   | 0.421875         | 23.416 |
| $\frac{28}{64}$ | 0.4375         | 11.113   | 0.4375           | 23.813 |
| $\frac{29}{64}$ | 0.453125       | 11.509   | 0.453125         | 24.209 |
| $\frac{30}{64}$ | 0.46875        | 11.906   | 0.46875          | 24.606 |
| $\frac{31}{64}$ | 0.484375       | 12.303   | 0.484375         | 25.003 |
| $\frac{32}{64}$ | 0.5000         | 12.700   | 1.000            | 25.400 |
|                 | 1 mm = .03937" |          | 0.01" = .0254 mm |        |

### PLEASE USE THE FOLLOWING GUIDELINES WHEN PREPARING ARTWORK:

- Only art files that can be opened and edited in the following software applications will be accepted: Adobe Illustrator; Adobe InDesign; Adobe Photoshop; QuarkXPress (version 7 or earlier).
- Imprints must be set up with 1/8" clearance between any non-bleeding imprint elements and the die strike.
- Bleeds must be 1/8" on all sides.
- Type should be at least 6 pts. Include all type fonts or convert type to outlines/curves.
- Include all linked files. Placed photos must be at least 300 ppi resolution. Placed text/logos/line art must be at least 600 ppi resolution.